



Rewinder



HCR8009 Duplex Surface Rewinder

Application: suitable for slitting various papers, Masking paper.

Specification:

Machine Width:	1.0M/1.3M/1.6M	Max. Unwind O.D:	Ø1500mm
Rewind Core I.D:	Ø3"	Max. Rewind O.D:	Ø1500mm
Machine Speed:	250M / Min		

Feature:

1. Driven by one A.C motor with 2 stages type length counter to make machine stops accurately.
2. Equipped with separated shaft type unwind base, auto web guide and auto unwind tension controller.
3. Rewind tension is as surface friction type, working with auto unwind tension controller to make perfect winding on all finished rolls.
4. Slitting by shear cutter, which was designed for winding rough and defective rolls again to various required sizes.
5. Trimming unit is as suction blower, which has high performance and quick collecting for waste materials.

Optional Parts:

1. Unwind Pick-Up Lift : For loading jumbo roll on the machine quickly and time saving.
2. Shaftless Unwind Base : Separated type with hydraulic core chuck can be equipped for efficient and quick performance on jumbo roll change.
3. Connected Splice Table : Splicing materials smoothly in order to decrease production loss.

(For reference only)



Hengcheng Machinery Co.,Ltd.

Manual and Automatic Single/Double Knife Roll Slitters and Slitter/Rewinders

E-mail: info@slitting-rewinder.com

URL: www.slitting-rewinder.com

Tel: +86-512-53100920

Fax: +86-512-53100720